



UL 标准 / UL Standard:	B	C	D
额定电压 / 电流 / Rated Voltage (V) / Current (A)	150 / 5	/	/
EC 标准 / IEC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III / 3	III / 2	II / 2
额定电压 / 电流 / Rated Voltage (V) / Current (A)	/	160	320
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	2.5	2.5	2.5
间距 / Pitch (mm) / 线数范围 / Poles	3.5 / N=04~48P		
使用温度范围 / Operating temperature (°C)	-40~+130		
符合RoHS环保要求 / Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:
STATUS:
APPD:
CHKD:
DRFT:

NAME: **宁波三安电子科技有限公司**
Sanan Electrical Technology Co. Ltd

DRAWING NO.: **5ESAKDHM-2.54**
DRFT: TYPE: SCALE: SHEET: 1/1

公差 / General tolerances (mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	